



• New 2020 S1 TITAN

Module	S1 TITAN Model 800	S1 TITAN Model 500S	S1 TITAN Model 500
Detector	Graphene window SDD, 20mm ² active area Typical resolution <145eV at 450kcps		
Detector Shield™	Included		
Color CMOS Camera	Optional		
Excitation Source	Rh target X-ray tube, 4W. 6-50kV, 5-200µA	Rh target X-ray tube, 2W. 15-29kV, 5-100µA	Rh target X-ray tube, 2W. 15-40kV, 5-100µA
Spot size	8mm standard, 5 or 3mm optional	8mm	
Filter	Five (5) position automatic filter changer	No filter	Fixed filter
Elemental Range	Mg - U		Ti - U
Sample Temperature	Default to 150°C (302°F) with Ultralene® window. Up to 350°C (662°F) with Kapton® window. (max. 5 sec measurement, min. 60 sec cool down).		to 350°C (662°F) with Kapton® window. (max. 5 sec measurement, min. 60 sec cool down).
Weight	1.5 kg (3.3 lbs) with battery		
Dimensions	25 cm x 28 cm x 9 cm (10 in x 11 in x 3.7 in) L x W x H		
Testing Modes	Assay, Grade ID, Grade Pass/Fail, Limit testing		
Operating Environment	Operating Temp: -10°C to +50°C (+14°F to 122°F); Altitude: ≤ 2,500 meters (8,200 ft.) Splash/dust resistant enclosure		
Power	Li-Ion battery (7.2V nominal); Battery Charger; AC Adapter (9V DC @ 3A)		
Display	9.4 cm (3.7 inch); LCD (TFT active matrix); 640 x 480 pixels; 64k color; resistive touchscreen		
Software	Bruker S1 proprietary software		
PC Operating System PC Software	Windows® 7 or Windows® 10 Microsoft® Excel or Bruker proprietary software for report generation and spectrum viewing		
Data Storage	512MB Internal; external USB data storage		
Data Transfer	USB 2.0, 802.11g/n 2.4GHz connectivity		
System Safety	Password protection; no sample (backscatter) shutoff, IR proximity sensor		
Languages	Chinese, Chinese simplified, Dutch, English, French, French Canadian, German, Indonesian, Italian, Japanese, Korean, Polish, PortugueseBR, Russian, SpanishMEX, SpanishSPN, Thai, Turkish		
Certification	CE, cTUVus		

Bruker is continually improving its products and reserves the right to change specifications without notice. © Bruker GJS 08-2020 P/N: 040.0079.06.0